Robert Trépanier, Canada

3

5

Turn the kite over so the front

(decorated) side

faces up. Tie kite

the spars, where


they cross in the middle of the vent. Use two overhand (shoelace-style)

knots.

Draw-your-own Instructions

• Materials, per kite •


- Two pieces of 11" x 17" bond paper, 20-lb. or 24-lb. bond paper
- Two 17-1/4-inch bamboo spars. You can use lightweight bamboo skewers from the grocery or garden store, but you may need to tape two skewers together for length.
- Kite line and winder
- Scissors
- Scotch tape



Fold the first piece of paper in half, as indicated.

Tape triangular А A sections (A) to the bottom of the sail, with 90° angle toward the outside of the sail, as shown. Decorate the unprinted, untaped side of the kite sail and tail, if you wish, with markers, crayons, paint, or collage. But remember: keep it light; weight affects flight. On the back (taped, undecorated) side of the sail, tape the spars in place, as shown.

Cut lengthwise strips, as shown, from the second piece of 11" x 17" bond paper. Tape the pieces end to end to make a long tail. Tape this tail to the ends of the triangular sections, as shown below, to make a long loop.



Cut out kite sail and tail pieces, per measurements indicated. Cut out trapezoidal vent (B) in the middle of the sail and discard.



2

